

Transponder

HG 70653ZA

Functional Description

The transponders are operated at 128 kHz.

The transmitting antenna of the reading unit supplies the transponder with energy by using an alternating field of 128 kHz. This induces a voltage within the coil of the transponder, which generates a current that is sufficient power supply for the electronics.

The system operates through fluid, gaseous as well as solid material.

However, if mounted directly on or within metal, the transponder's reading distance is influenced and the positioning signal may be distorted.



Read-Write-Transponder (RW)

The Read-Write transponders are equipped with an EEPROM in which the code is stored. The EEPROM may be rewritten up to more than 100,000 times.



Technical Data

Function	Antenna HG 98860
Outer diameter	ø 73 mm
Mounting hole	ø 5 mm
Thickness	15 mm
Weight	100 g
Material	Durethan casing filled with Polyurethan compound
Reading time	8 ms
Operating temperature	-20 to +60° C
Storage temperature	-20 to +60° C
Mechanical pressure	max. 490 N/cm ²
Protection class	IP 67
Reading system, read write	PSK
Operating frequency	128 kHz / 64 kHz
Useful data	20 Bit
Min. distance between two transponders	1.5-times the antenna width
Programming device	HG 81830YA
Reading distance	150 - 350 mm Nominal reading distance: 200 mm

Application Examples from the Automation Industry

♦ Automated Guided Vehicles (AGV):

- Positioning
- Track Guidance
- Identification

